

ersion: 2.0	Revision Date: 22	2.04.2020	Print Date: 22/04/2020
onforms to EU Regulation 190 ECTION 1: Identification			
1.1 Product identifier			
Trade name	: Valvoline [™]	COCKPITSPRAY I	-OAM
Product code	: 887083		
Recommended use 1.3 Details of the supplie	: Cleaner.	1.4 Emergency te	lephone number
sheet Ellis Enterprises B.V., an a Wieldrechtseweg 39 3316 BG Dordrecht Netherlands	ffiliate of Valvoline		001-859-202-3865, or contact icy telephone number at +31
+31 (0)78 654 3500 (in the contact your local CSR cor			on 0 (in the Netherlands), or CSR contact person
SDS@valvoline.com			

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)Aerosols, Category 1H223: Flammable aerosol.H229: Pressurised container: May burst if heated.Eye irritation, Category 2H319: Causes serious eye irritation.

2.2 Label elements

UFI

1TXQ-EM3M-KT47-TY5Y

Labelling (REGULATION (EC) No 1272/2008)

:



Version: 2.0	Revision Date: 2	2.04.2020	Print Date: 22/04/2020
Hazard pictograms			
Signal word	: Danger		
Hazard statements	: H222 H229 H319	Extremely flamma Pressurised conta Causes serious ey	iner: May burst if heated.
Precautionary statements	: P101	If medical advice is container or label	s needed, have product at hand.
	P102 Prevention :	Keep out of reach	of children.
	P210		eat, hot surfaces, sparks, other ignition sources. No
	P211		n open flame or other
	P251	5	urn, even after use.
	P260	Do not breathe spi	
	Storage:		-
	P410 + P412		ght. Do not expose to eeding 50 °C/ 122 °F.
	Disposal:	•	-
	P501	Dispose of conten accordance with lo	

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Additional advice No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
	EC-No.	(REGULATION (EC)	
	Registration number	No 1272/2008)	
propan-2-ol	67-63-0	Flam. Liq.2; H225	>= 15,00 - < 20,00
2 / 19			



Version: 2.0	Revision Date: 22.04.2020		Print Date: 22/04/2020
	200-661-7 01-2119457558-25-xxxx	Eye Irrit.2; H319 STOT SE3; H336	
Ammonia, aqueous solution	1336-21-6 215-647-6	Acute Tox.4; H302 Skin Corr.1B; H314 STOT SE3; H335 Aquatic Acute1; H400 Aquatic Chronic2; H411	>= 0,25 - < 0,50
Substances with a workp 1-Methoxypropan-2-ol	lace exposure limit : 107-98-2 203-539-1 01-2119457435-35-xxxx	Flam. Liq.3; H226 STOT SE3; H336	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures	6
General advice :	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled :	If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact :	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed :	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
4.2 Most important symptoms and e	ffects, both acute and delayed

Symptoms : No symptoms known or expected.



Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020
Risks	: Causes serious eye irritation. Repeated exposure may cause s	skin dryness or cracking.
4.3 Indication of any immediate r	nedical attention and special treatr	ment needed
Treatment	: No hazards which require specia	l first aid measures.
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use extinguishing measures that circumstances and the surroundi Water spray Foam Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	: High volume water jet	
5.2 Special hazards arising from	the substance or mixture	
Specific hazards during firefighting	 Never use welding or cutting torce empty) because product (even jue explosively. Beware of vapours accumulating concentrations. Vapours can accord Do not allow run-off from fire figh courses. 	ist residue) can ignite to form explosive sumulate in low areas.
Hazardous combustion products	: carbon dioxide and carbon mono Hydrocarbons	oxide
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-con	tained breathing apparatus.
Specific extinguishing methods	: Product is compatible with standa	ard fire-fighting agents.
Further information	: Fire residues and contaminated f be disposed of in accordance wit	



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Evacuate personnel to safe areas.
r ereena procadiene	Remove all sources of ignition.
	Ensure adequate ventilation.
	Beware of vapours accumulating to form explosive
	concentrations. Vapours can accumulate in low areas.
	Persons not wearing protective equipment should be excluded
	from area of spill until clean-up has been completed.
	Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against : Take necessary action to avoid static electricity discharge



Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020
fire and explosion	(which might cause ignition of org from open flames, hot surfaces a only explosion-proof equipment.	
Hygiene measures	: Wash hands before breaks and a using do not eat or drink. When u	
7.2 Conditions for safe storage	e, including any incompatibilities	
Requirements for storage areas and containers	: BEWARE: Aerosol is pressurized exposure and temperatures over or throw into fire even after use. I red-hot objects. Keep container ti well-ventilated place. Containers carefully resealed and kept uprigh Observe label precautions. No sn	50 °C. Do not open by force Do not spray on flames or ightly closed in a dry and which are opened must be ht to prevent leakage.
Other data	: No decomposition if stored and a	pplied as directed.
7.3 Specific end use(s) Specific use(s)	: No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1-Methoxypropan-2-ol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
		STEL	150 ppm 568 mg/m3	2000/39/EC
		TLV-8hr	375 mg/m3	NL WG
		TLV-15 min	563 mg/m3	NL WG

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.



Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020
Personal protective equip	ment	
Eye protection	: Wear chemical splash goggles whe exposure of the eyes to liquid, vapo	
Hand protection		
Remarks	: The suitability for a specific workpla with the producers of the protective	
Skin and body protection	: Wear as appropriate: Impervious clothing Safety shoes Flame-resistant clothing Choose body protection according t concentration of the dangerous sub	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	aerosol
Colour	:	colourless
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	2 %(V)



SAFETY DATA SHEET

Valvoline™ COCKPITSPRAY FOAM

Revision Date: 22.04.2020	Print Date: 22/04/2020
: 43 hPa (20 °C)	
: No data available	
: No data available	
: 0,89 g/cm3 (20 °C)	
: immiscible	
: No data available	
: No data available	
: 425 °C	
: No data available	
: not auto-flammable	
	 43 hPa (20 °C) No data available No data available 0,89 g/cm3 (20 °C) immiscible No data available No data available 425 °C No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Vapours may form explosive mixture with air.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid

: Exposure to air or moisture over prolonged periods.



Revision Date: 22.04.2020 Version: 2.0 Print Date: 22/04/2020 Heat, flames and sparks. **10.5 Incompatible materials** Materials to avoid : Acids Aldehydes alkalis aluminum Amines Ethylene oxide Halogenated hydrocarbons halogens isocyanates salts of strong bases strong bases Strong oxidizing agents Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

10.6 Hazardous decomposition products

Hazardous decomposition products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information.

Components:	
ISOPROPANOL:	
Acute oral toxicity	: LD50 (Rat): 5,84 g/kg
Acute inhalation toxicity	: LC50 (Rat): 16000 ppm Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	: LD50 (Rabbit): 12.800 mg/kg



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

Components: AMMONIUM HYDROXIDE ((NH4)(OH)): Acute oral toxicity : LD50 (Rat): 350 mg/kg Components: 1-METHOXY-2-PROPANOL:

Acute oral toxicity	:	LD50 (Rat): 4.016 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 10000 ppm Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 13.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ISOPROPANOL:

Result: Slight, transient irritation

AMMONIUM HYDROXIDE ((NH4)(OH)): Result: Corrosive to skin

1-METHOXY-2-PROPANOL: Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

	OPANOL:	
Result:	Irritating to	eyes.



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

AMMONIUM HYDROXIDE ((NH4)(OH)):

Result: Corrosive

1-METHOXY-2-PROPANOL:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

1-METHOXY-2-PROPANOL:

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

1-METHOXY-2-PROPANOL:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro
	Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Product:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Components:

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

AMMONIUM HYDROXIDE ((NH4)(OH)):

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

1-METHOXY-2-PROPANOL:

Assessment: May cause drowsiness or dizziness.



Version: 2.0

Ш

Revision Date: 22.04.2020

Print Date: 22/04/2020

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product: Remarks: No data available

Components:

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:

: LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450 mg/l Exposure time: 96 h Test Type: flow-through test
: LC50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 24 h Test Type: static test
: LC50 (Pimephales promelas (fathead minnow)): 8,5 mg/l Exposure time: 96 h
: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test
: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test



Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020	
Toxicity to algae	: EC50 (Pseudokirchneriella subcapi 1.000 mg/l End point: Growth inhibition Exposure time: 7 d Test Type: static test	tata (green algae)): >	

12.2 Persistence and degradability

Components:

1-Methoxypropan-2-ol	
Biodegradability	: Result: Readily biodegradable. Biodegradation: 96 % Exposure time: 28 d Method: OECD Test Guideline 301E

12.3 Bioaccumulative potential

Components:

propan-2-ol		
Partition coefficient: n- octanol/water	: log Pow: 0,05	

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:	
Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher
12.6 Other adverse effects	
Product:	

Additional ecological	:	An environmental hazard cannot be excluded in the event of
information		unprofessional handling or disposal., Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: The product should not be allowed to enter drains, water



Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020
	courses or the soil. Do not contaminate ponds, waterways of chemical or used container. Send to a licensed waste management	
Contaminated packaging	 Empty remaining contents. Empty containers should be taken to an handling site for recycling or disposal. Do not re-use empty containers. Do not burn, or use a cutting torch on, the second second	

SECTION 14: Transport information

14.1 UN number

	ADN	:	UN 1950
	ADR	:	UN 1950
	RID	:	UN 1950
	IMDG	:	UN 1950
	ΙΑΤΑ	:	UN 1950
14.2	UN proper shipping name		
	ADN	:	AEROSOLS
	ADR	:	AEROSOLS
	RID	:	AEROSOLS
	IMDG	:	AEROSOLS
	ΙΑΤΑ	:	AEROSOLS
14.3	Transport hazard class(es)		
	ADN	:	2
	ADR	:	2
	RID	:	2
	IMDG	:	2.1
	ΙΑΤΑ	:	2.1
14.4	Packing group		
	ADN		



SAFETY DATA SHEET

Valvoline™ COCKPITSPRAY FOAM

Version: 2.0	Revision Date: 22.04.2020	Print Date: 22/04/2020
Labels ADR	: 2.1	
Packing group Classification Code Labels Tunnel restriction code RID	 Not assigned by regulation 5F 2.1 (D) 	
Packing group Classification Code Hazard Identification Number Labels IMDG	 Not assigned by regulation 5F 23 2.1 	
Packing group Labels EmS Code	 Not assigned by regulation 2.1 F-D, S-U 	
IATA (Cargo)		
Packing instruction (cargo aircraft) Packing instruction (LQ)	: 203	
Packing Instruction (LQ) Packing group	: Y203 : Not assigned by regulation	
Labels	: Flammable Gas	
IATA (Passenger)		
Packing instruction (passenger aircraft)	: 203	
Packing instruction (LQ)	Y203	
Packing group Labels	: Not assigned by regulation : Flammable Gas	
14.5 Environmental hazards		
ADN		
Environmentally hazardous	: no	
ADR Environmentally hazardous	: no	
RID Environmentally hazardous	: no	
IMDG Marine pollutant	: no	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1	Safety, health and environment	tal regulations/legislati	on s	specific for the sub	ostance or mixture
	Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			Not applicable	
	Regulation (EC) No 850/2004 on pollutants	persistent organic	:	Not applicable	
	REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable	
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			Not applicable	
Regulation (EC) No 649/2012 of the European : Not applicable Parliament and the Council concerning the export and import of dangerous chemicals			Not applicable		
	REACH - Restrictions on the manufacture, placing on : Not applicable the market and use of certain dangerous substances, preparations and articles (Annex XVII)				
	Seveso III: Directive 2012/18/EU major-accident hazards involving		ent		on the control of
	P3a	FLAMMABLE AEROSO	DLS	Quantity 1 150 t	Quantity 2 500 t
	18	Liquefied extremely flammable gases (inclu LPG) and natural gas	dinę	50 t g	200 t

General Assessment Methodology (GAM)



Version: 2.0	Revision Date:	22.04.2020	Print Date: 22/04/2020
Aquatic harmfulness	properties f	n biodegradable substances or humans and the environm y/ reprotoxicity/ bioacumulat).	nent (carcinogenicity/
Abatement effort		ostances of Very High Conce that are most hazardous for tt.	
Regulation (EC) No. 648/2004, as amended	: 5 % or over	but less than 15 %: Aliphati	c hydrocarbons
The components of this p	duct are report	ed in the following invento	ories:
DSL	•	ents of this product are on th	
AICS	: On the inve	ntory, or in compliance with	the inventory
ENCS	: On the inve	ntory, or in compliance with	the inventory
KECI	: On the inve	ntory, or in compliance with	the inventory
PICCS	: On the inve	ntory, or in compliance with	the inventory
IECSC	: On the inve	ntory, or in compliance with	the inventory
TCSI	: On the inve	ntory, or in compliance with	the inventory
TSCA	: On TSCA li	nventory	

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16:	Other	information
--------------------	-------	-------------



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

Further information

Internal information : 000000274855

Full	text	of	H-Statements
		•••	

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA). ICAO : International Civil Aviation Organization



Version: 2.0

Revision Date: 22.04.2020

Print Date: 22/04/2020

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level ABM : Water Hazard Class for the Netherlands ADR : Agreement concerning the International Carriage of Dangerous Goods by Road. ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP : Classification, Labelling and Packaging

CSA : Chemical Safety Assessment

CSR : Chemical Safety Report

DNEL : Derived No Effect Level.

EINECS : European Inventory of Existing Commercial Chemical Substances.

ELINCS : European List of Notified Chemical Substances

PEC : Predicted Effect Concentration

PEL : Permissible Exposure Limits

PNEC : Predicted No Effect Concentration

R-phrase : Risk phrase

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulation Concerning the International Transport of Dangerous Goods by Rail S-phrase: Safety phrase

WGK : German Water Hazard Class