



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS\_NL

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name : Tectyl™ CAVITY WAX AMBER  
RUST PREVENTATIVE

Product code : 887096

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : Corrosion inhibitor.

**1.3 Details of the supplier of the safety data sheet**

Ellis Enterprises B.V., an affiliate of Valvoline  
Wieldrechtseweg 39  
3316 BG Dordrecht  
Netherlands  
+31 (0)78 654 3500 (in the Netherlands), or  
contact your local CSR contact person

SDS@valvoline.com

**1.4 Emergency telephone number**

00-800-825-8654 / 001-859-202-3865, or contact  
your local emergency telephone number at +31  
030 274 88 88

**Product Information**

+31 (0)78 654 3500 (in the Netherlands), or  
contact your local CSR contact person

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification (REGULATION (EC) No 1272/2008)**

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single  
exposure, Category 3, Central nervous  
system

H336: May cause drowsiness or dizziness.

**2.2 Label elements**

UFI : HS2C-6CDR-Y009-C41Y



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H336 May cause drowsiness or dizziness.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
**Storage:**  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:  
Naphtha (petroleum), hydrotreated heavy

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**Additional advice**

No information available.

---

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Naphtha (petroleum), hydrotreated heavy	64742-48-9 919-857-5 01-2119463258-33-xxxx	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304	>= 20,00 - < 25,00
Sulfonic acids, petroleum, sodium salts	68608-26-4 271-781-5 01-2119527859-22-xxxx	Eye Irrit.2; H319	>= 1,00 - < 2,50
(Z)-N-methyl-N-(1-oxo- 9-octadecenyl)glycine	110-25-8	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute1; H400 Aquatic Chronic3; H412	>= 0,10 - < 0,25
Substances with a workplace exposure limit :			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7 01-2119471299-27-xxxx		>= 1,00 - < 2,50
(2- Methoxymethylethoxy)p ropanol	34590-94-8 252-104-2 01-2119450011-60-xxxx		>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms : No symptoms known or expected.

Risks : May cause drowsiness or dizziness.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : No hazards which require special first aid measures.  
Treat symptomatically.

---

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

**5.3 Advice for firefighters**

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against : Do not spray on a naked flame or any incandescent material.



# SAFETY DATA SHEET

Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Other data : No decomposition if stored and applied as directed.

## 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TLV-8hr (Mist)	5 mg/m3 Mist	NL WG
(2-Methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m3	2000/39/EC
		TLV-8hr	300 mg/m3	NL WG

### 8.2 Exposure controls

#### Personal protective equipment



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

---

Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection	
Material	: nitrile rubber
Break through time	: 480 min
Glove thickness	: 0,38 mm
Remarks	: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.  The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: In the case of vapour formation use a respirator with an approved filter. In the case of dust or aerosol formation use respirator with an approved filter.
Filter type	: Combined particulates, organic gas and low boiling vapour type (AX-P)  Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to EN 143  Particulates type (P)

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: aerosol
Colour	: amber
Odour	: solvent-like
Odour Threshold	: No data available



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

---

pH	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	< 0 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0,70 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

**9.2 Other information**

Self-ignition : No data available





**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : excessive heat  
Exposure to air.  
Do not allow evaporation to dryness.

No data available  
Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Acids  
salts of strong bases  
strong bases  
Strong oxidizing agents

Not applicable

### 10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Acute oral toxicity	: LD50 (Rat, male and female): > 15.000 mg/kg Method: OECD Test Guideline 423 Remarks: The toxicological data has been taken from products of similar composition.
Acute inhalation toxicity	: LC50 (Rat): > 4,95 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: The toxicological data has been taken from products of similar composition.
Acute dermal toxicity	: LD50 (Rabbit, male and female): >= 3.160 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: The toxicological data has been taken from products of similar composition.

**Components:**

**SODIUM PETROLEUM SULFONATE:**

Acute oral toxicity	: LD50 (Rat): > 5 g/kg  LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401 GLP: yes Remarks: The toxicological data has been taken from products of similar composition.
Acute inhalation toxicity	: LC50 (Rat): > 1,9 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 GLP: yes Assessment: The component/mixture is minimally toxic after short term inhalation. Remarks: No mortality observed at this dose. The toxicological data has been taken from products of similar composition.
Acute dermal toxicity	: LD50 (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402 GLP: yes Remarks: No mortality observed at this dose. The toxicological data has been taken from products of similar



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

composition.

**Components:**

**OLEYL N-METHYLGLYCINE:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 1,01 - 1,85 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

**Components:**

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

**Components:**

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC0 (Rat, female): > 553 ppm  
Exposure time: 8 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Remarks: No mortality observed at this dose.  
Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:**

Result: Slight, transient irritation

**SODIUM PETROLEUM SULFONATE:**

Species: Rabbit  
Result: Slight, transient irritation  
Remarks: The toxicological data has been taken from products of similar composition.

**OLEYL N-METHYLGLYCINE:**

Result: Irritating to skin.

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Result: Slight, transient irritation

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Species: Rabbit

Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:**

**Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:**

Result: No eye irritation

**SODIUM PETROLEUM SULFONATE:**

Species: Rabbit

Result: Irritating to eyes.

Remarks: The toxicological data has been taken from products of similar composition.

**OLEYL N-METHYLGLYCINE:**

Result: Corrosive

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Result: Slight, transient irritation

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Species: Rabbit

Result: Slight, transient irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:**

**SODIUM PETROLEUM SULFONATE:**

Assessment: Does not cause skin sensitisation.

Remarks: The toxicological data has been taken from products of similar composition.

**OLEYL N-METHYLGLYCINE:**

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Species: **Humans**  
Assessment: **Does not cause skin sensitisation.**

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**SODIUM PETROLEUM SULFONATE:**

Genotoxicity in vitro : Test Type: **Ames test**  
Test species: **Salmonella typhimurium**  
Metabolic activation: **with and without metabolic activation**  
Result: **negative**  
Remarks: **The toxicological data has been taken from products of similar composition.**

**OLEYL N-METHYLGLYCINE:**

Genotoxicity in vitro : Test Type: **Ames test**  
Test species: **Salmonella typhimurium**  
Metabolic activation: **with and without metabolic activation**  
Result: **negative**

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Genotoxicity in vitro : Test Type: **Ames test**  
Test species: **Salmonella typhimurium**  
Metabolic activation: **with and without metabolic activation**  
Result: **negative**

**Carcinogenicity**

Not classified based on available information.

**Components:**

**Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:**

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

**Components:**

**Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:**

Assessment: **May cause drowsiness or dizziness.**

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:**

**May be fatal if swallowed and enters airways.**

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

**No aspiration toxicity classification**

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:**

**DIPROPYLENE GLYCOL MONOMETHYL ETHER:**

Remarks: **Central nervous system**

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:**

Naphtha (petroleum), hydrotreated heavy



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Toxicity to fish	: LL50 ( <i>Oncorhynchus mykiss</i> (rainbow trout)): > 1.000 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 ( <i>Daphnia magna</i> (Water flea)): 1.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: EL50 ( <i>Pseudokirchneriella subcapitata</i> (green algae)): > 1.000 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201

Sulfonic acids, petroleum, sodium salts

Toxicity to fish	: LL50 ( <i>Pimephales promelas</i> (fathead minnow)): > 1.000 mg/l Exposure time: 96 h Test Type: Renewal Test substance: WAF Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	: EC50 ( <i>Daphnia magna</i> (Water flea)): > 1.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to algae	: NOEC ( <i>Pseudokirchneriella subcapitata</i> (green algae)): > 1.000 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Remarks: The toxicological data has been taken from products of similar composition.

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Toxicity to fish	: LC50 ( <i>Leuciscus idus</i> (Golden orfe)): 0,93 mg/l Exposure time: 96 h Test Type: static test
------------------	---



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0,43 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): 6,3 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test
M-Factor (Short-term (acute) aquatic hazard)	: 1

Ecotoxicology Assessment  
Short-term (acute) aquatic hazard :

Long-term (chronic) aquatic hazard	: Acute aquatic toxicity Category 1; Very toxic to aquatic life. Harmful to aquatic life with long lasting effects. Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.
------------------------------------	---

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.





**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

(2-Methoxymethylethoxy)propanol

Toxicity to fish	: LC50 ( <i>Pimephales promelas</i> (fathead minnow)): > 10.000 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: LC50 ( <i>Daphnia magna</i> (Water flea)): 1.919 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 ( <i>Pseudokirchneriella subcapitata</i> (green algae)): > 969 mg/l End point: Growth inhibition Exposure time: 72 h

**12.2 Persistence and degradability**

**Components:**

Naphtha (petroleum), hydrotreated heavy

Biodegradability	: Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

Sulfonic acids, petroleum, sodium salts

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 8 % Exposure time: 28 d Method: OECD Test Guideline 301D Remarks: The toxicological data has been taken from products of similar composition.
------------------	--

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Biodegradability	: Result: Inherently biodegradable. Method: OECD Test Guideline 301F
------------------	---

(2-Methoxymethylethoxy)propanol

Biodegradability	: Result: Readily biodegradable. Biodegradation: 75 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

Chemical Oxygen Demand (COD) : 2,02 mg/g

ThOD : 2,06 mg/g



# SAFETY DATA SHEET

Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

## 12.3 Bioaccumulative potential

### Components:

Sulfonic acids, petroleum, sodium salts

Partition coefficient: n-octanol/water : log Pow: **Calculated > 10**

(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

Partition coefficient: n-octanol/water : log Pow: **3,5 - 4,2**

(2-Methoxymethylethoxy)propanol

Partition coefficient: n-octanol/water : log Pow: **0,004**

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Other adverse effects

### Product:

Further information : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Contaminated packaging : Send to a licensed waste management company.  
: Empty remaining contents.  
: Dispose of as unused product.  
: Do not re-use empty containers.  
: Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14: Transport information**

**14.1 UN number**

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

**14.2 UN proper shipping name**

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : AEROSOLS

**14.3 Transport hazard class(es)**

**ADN** : 2  
**ADR** : 2  
**RID** : 2  
**IMDG** : 2.1  
**IATA** : 2.1

**14.4 Packing group**

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
**ADR**  
Packing group : Not assigned by regulation



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**14.5 Environmental hazards**

**ADN**

Environmentally hazardous : no

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Netherlands. Substances of very high concern (ZZS-list) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

		Quantity 1	Quantity 2
8	Extremely flammable	10 t	50 t
9b	Dangerous for the environment	200 t	500 t
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.			
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a)	2.500 t	25.000 t



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

gasolines and naphthas,  
(b) kerosenes (including jet  
fuels), (c) gas oils  
(including diesel fuels,  
home heating oils and gas  
oil blending streams),(d)  
heavy fuel oils (e)  
alternative fuels serving the  
same purposes and with  
similar properties as  
regards flammability and  
environmental hazards as  
the products referred to in  
points (a) to (d)

**General Assessment Methodology (GAM)**

- Aquatic harmfulness : Z2 Biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ noreprotoxicity/ bioaccumulative potential or toxicity)
- Abatement effort : Z Substances of Very High Concern, SVHC: set of substances that are most hazardous for humans and the environment.
- Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 1,1 %

**Other regulations:**

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

**The components of this product are reported in the following inventories:**

- TCSI : On the inventory, or in compliance with the inventory
- TSCA : All substances listed as active on the TSCA inventory
- AIIC : All components are listed on the inventory, regulatory



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

obligations/restrictions apply

DSL	:	All components of this product are on the Canadian DSL
ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory
TECI	:	Not in compliance with the inventory

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**15.2 Chemical safety assessment**

No data available

---

**SECTION 16: Other information**

**Further information**

Internal information : R0524073

**Full text of H-Statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.



**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
<b>H332</b>	Harmful if inhaled.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H400</b>	Very toxic to aquatic life.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development





**SAFETY DATA SHEET**  
Tectyl™ CAVITY WAX AMBER RUST  
PREVENTATIVE

Version: 7.0

Revision Date: 16.02.2022

Print Date: 17/02/2022

---

OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands  
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine  
CLP : Classification, Labelling and Packaging  
CSA : Chemical Safety Assessment  
CSR : Chemical Safety Report  
DNEL : Derived No Effect Level.  
EINECS : European Inventory of Existing Commercial Chemical Substances.  
ELINCS : European List of Notified Chemical Substances  
PEC : Predicted Effect Concentration  
PEL : Permissible Exposure Limits  
PNEC : Predicted No Effect Concentration  
R-phrase : Risk phrase  
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail  
S-phrase: Safety phrase  
WGK : German Water Hazard Class