



# Tork Cleaning Cloth Combi Roll

Kleur: Wit Format: Combi Roll in Box



## voordeel

- exelCLEAN voor meer efficiëntie bij het schoonmaken
- Multifunctioneel – de meeste oppervlakken in een veeg schoon
- Zacht en flexibel – ideaal in nauwe ruimtes
- Goedgekeurd voor gebruik met voedingsmiddelen



400



152 m



1



## producteigenschappen

artikel	systeem	Rollengte	Roldiameter	Aantal vellen	Lagen	Print	Kleur
510137	W1 - Poetsdoeken muur/vloer/stand aard systeem, W2 - Poetsdoeken combi rol systeem, W3 - Poetsdoeken pak systeem	152 m	25 cm	400	1	nee	Wit



# Tork Cleaning Cloth Combi Roll

Kleur: Wit Format: Combi Roll in Box

## verzendgegevens

### consumentenunit

<b>EAN</b>	7322540057263
<b>stuks</b>	1
<b>hoogte</b>	338 mm
<b>breedte</b>	264 mm
<b>lengte</b>	264 mm
<b>volume</b>	23.6 dm <sup>3</sup>
<b>nettogewicht</b>	2675 g
<b>brutogewicht</b>	2993 g

### transportunit

<b>EAN</b>	7322540057270
<b>stuks</b>	1
<b>consumentenunits</b>	1
<b>materiaal</b>	Carton
<b>hoogte</b>	338 mm
<b>breedte</b>	264 mm
<b>lengte</b>	264 mm
<b>volume</b>	23.6 dm <sup>3</sup>
<b>nettogewicht</b>	2.68 kg
<b>brutogewicht</b>	2.99 kg

### pallet

<b>EAN</b>	7322540195521
<b>stuks</b>	72
<b>consumentenunits</b>	72
<b>hoogte</b>	2178 mm
<b>breedte</b>	800 mm
<b>lengte</b>	1200 mm
<b>volume</b>	1.7 m <sup>3</sup>
<b>nettogewicht</b>	192.60 kg
<b>brutogewicht</b>	215.50 kg



# Tork Cleaning Cloth Combi Roll

Kleur: Wit Format: Combi Roll in Box

---

## milieu

### Content

Chemical pulp Polypropene Polyester Chemicals

### Material

**Chemical pulp** Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product.

**Polypropene** Polypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. **Polyester** Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. **Chemicals** Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a polyamide (from polyamidine/epichlorhydrine polymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

### Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

### Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.