



Tork Heavy-Duty Cloth Folded

Kleur: Wit Format: Folded



voordeel

- exelCLEAN voor meer efficiëntie bij het schoonmaken
- Multifunctioneel – de meeste oppervlakken in een veeg schoon
- Hoog absorptievermogen van vloeistoffen en olie
- Sterk genoeg voor het zwaardere reinigingswerk
- Goedgekeurd voor gebruik met voedingsmiddelen



producteigenschappen

artikel	stelsysteem	Lagen	Print	Kleur
530150	W8 - Poetsdoeken klein pakket	1	nee	Wit

verzendinggegevens

consumenteenheid

EAN	7322540238280
stuks	45
materiaal	Plastic
hoogte	89 mm
breedte	160 mm
lengte	195 mm
volume	2.8 dm ³
nettogewicht	444 g
brutogewicht	450 g

transportunit

EAN	7322540238297
stuks	360
consumenteenheids	8
materiaal	Carton
hoogte	182 mm
breedte	400 mm
lengte	400 mm
volume	29.1 dm ³
nettogewicht	3.55 kg
brutogewicht	4.20 kg

pallet

EAN	7322540239164
stuks	21600
consumenteenheids	480
hoogte	2 mm
breedte	800 mm
lengte	1 mm
volume	1.7 m ³
nettogewicht	212.89 kg
brutogewicht	251.76 kg



Tork Heavy-Duty Cloth Folded

Kleur: Wit Format: Folded

milieu

Content

Chemical pulp Polypropene Polyester Chemicals

Material

Chemical pulp Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product.

Polypropene Polypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Polyester Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength. The fibre used contains black pigments.

Chemicals Both functional and process chemicals are used. The functional chemical used is wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

Production

The material is produced at Suameer mill, NL, certified according to ISO 9001:2000, ISO 14001 and EMAS. Product converted externally in DE.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.