

voordeel

 Goedgekeurd voor gebruik met voedingsmiddelen











producteigenschappen

artikel	systeem	Rollengte	Roldiameter	Aantal vellen	Binnenste diameter van kern	Lagen	Print	Reliëf	Kleur
129239	W1 - Poetsdoeken muur/vloer/st andaard systeem	680 m	38.5 cm	2000	7.1 cm	2	nee	ja	Wit



verzendgegevens

consumentenunit

EAN	7322540019636
stuks	1
hoogte	369 mm
breedte	385 mm
lengte	385 mm
volume	54.7 dm3
nettogewicht	9280 g
brutogewicht	9500 g

transportunit

EAN	7322540019636		
stuks	1		
consumentenunit s	1		
materiaal	Plastic		
hoogte	369 mm		
breedte	385 mm		
lengte	385 mm		
volume	54.7 dm3		
nettogewicht	9.28 kg		
brutogewicht	9.50 kg		

pallet

EAN	7322540205398		
stuks	30		
consumentenunit s	30		
hoogte	1995 mm		
breedte	800 mm		
lengte	1200 mm		
volume	1.6 m3		
nettogewicht	278.40 kg		
brutogewicht	285.00 kg		



milieu

Content

Recycled fibres, Chemicals

Material

Recycled fibresRecovered paper can be produced both from collected newsprint, magazines and office waste. The paper is washed with water and treated with chemicals under high temperature and then filtered. Different fibres demand different processes and this determines the end product properties, and makes the fibre type (recovered or virgin) less important. The environmental benefits and economic feasibility of recovered paper as a raw material source depend on its availability, transport distance and the quality of the collected material. Bleaching of fibresBleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety. There are different methods used today for bleaching ECF (elementary chlorine free(where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view . The used functional chemicals are:Wetstrength agentDry strength agentDye=if coloured Fixing agentsFluorescent whitening agentGlue=if usedSoftenersThe process chemicals are:AntipitchProtection agentYankee coatingDefoamerDispersing agents and surfactantspH and charge controlRetention aidsBroke treatment chemicalsDrainage aid

Packaging

Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label = EcolabelThis product does not have any ecolabel.

Date of issue 2010-02-25

Revision date

Production

This product is produced at Kostheim mill, Germany, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.



